




ISUZU D-MAX & MU-X | MAZDA BT-50 2020 - CURRENT

TOWING MIRRORS INSTALLATION GUIDE



Towing Mirrors



Power Boards



Rock Tamers



Tyre Spider



Easy Slides



Power Slides



Expana Slides



Fridge Cage




Pantry




Cutlery Set



Clip on Trays



Cable Saver



Thank you for choosing Clearview Accessories®

When it comes to road safety, having full visibility of your vehicle and your caravan, trailer or horse float is paramount. Clearview Towing Mirrors extend your field of vision when towing, changing lanes or reversing, to help see you to your destination safely. From Cape York's Telegraph Track to the Gibb River Road, Clearview Towing Mirrors are purpose-built tough for Australian conditions!

Clearview Accessories began in 2006, as a family run business owned by entrepreneur Mike Cowan and his son-in-law Jay Praag. In the years that followed, Mike and Jay turned their small family business with three full-time employees, into one of Australia's most respected 4WD and Touring Brands.

With a strong passion for the automotive industry, quality design and discipline in professional workmanship, our trust is built within our values of creating high quality ADR compliant designs.

From humble beginnings, Clearview Accessories has grown and today manufactures a range of unique, quality products for your next off-road adventure!

Contact us:

Clearview Accessories,
3 Frog Court, Craigieburn VIC 3064
Phone: (03) 8351 9933
Email: info@clearviewaccessories.com.au
Website: clearviewaccessories.com.au

Find us on social media

-  facebook.com/clearviewaccessories
-  instagram.com/clearviewaccessories
-  youtube.com/CLEARVIEWACCESSORIES

Due to Clearview's Continuous Improvement Program, information may change without notice. Clearview takes no responsibility for the result of incorrect use of these installation instructions.

Our range	2
Introduction	3
Getting started	5
Before you Start	6
Maintaining your Mirrors	7
Mirror dimensions	8
Fitting instructions	10-18
FAQS	19
Troubleshooting	20-21
Warranty	22-23

Clearview mirrors are direct replacement mirrors that mount securely in the same position as your original mirrors.

What's in the box



- 1 x Left hand side mirror & base
- 1 x Right hand side mirror & base
- 1 x Installation instruction

If anything is missing, or damaged, please do not install your new mirrors and contact us on **03 8351 9933** or via: info@clearviewaccessories.com.au

Tools Required:

- 'S'-hook
- Ratchet with 10mm socket
- Soft plastic pry-bar (Trim remover)
- Phillips head screwdriver



Whilst our mirrors can be installed by one person, the process is quicker and easier when an additional person is available to hold the mirror into position.



CAUTION



WARNING

- Read through the fitting instructions before installation of Clearview Accessories.
- Always install the accessory following the fitting instructions. Failure to do so may cause damage to the vehicle or the accessory and will void your warranty.
- Ensure all packaging materials are recycled and/or disposed of in accordance with local regulations.
- It is always recommended that this accessory is fitted by a qualified technician.
- Safely store and protect any removed vehicle components.
- Ensure all bare metal surfaces are protected using Automotive Bare Metal Primer and touch-up paint.
- Remove all metal swarf and dust from all vehicle surfaces if the surface is used for accessory installation.
- Your vehicle may be fitted with the Active Park Assist feature. You should only use this feature with your Towing Mirrors in the fully retracted, driving position.



POWER FOLD

WARNING
DO NOT UNFOLD MANUALLY

If your mirror is equipped with Power Fold. In some cases, the mirror head may be loose before installation as the mirror head needs to be electrically folded and unfolded for a minimum of cycles on its first use to synchronise.

Please refrain from folding the mirror MANUALLY as it can reduce the life span of the product.

- NB: This mirror is designed to be manually folded upon impact as a safety feature.

COURTESY/PUDGLE LIGHT

Please understand that every car and every model is different and that some vehicles have different wiring options than other vehicles. We do not know the exact wiring configuration of your vehicle.

If you require the use of the courtesy/puddle light function you will require the assistance of an Auto Electrician.

- Clearview Accessories does NOT provide this service unless it's a standard function on the vehicle.

NB: Where there is an electrical modification of the vehicle, a suitably licenced person should undertake the work.

- IF HARD WIRING: **ORANGE WIRE: NEGATIVE (-) | GREY WIRE: POSITIVE (+)**

Maintaining Powder Coated Surfaces

Whilst powder coating is a lot more durable, and longer lasting than paint, it can still be affected by dust, dirt, salt water and constant exposure to the weather. For this reason, no protective powder coating is completely maintenance-free.

With the right maintenance, you can increase the life of the finish of your powder coated surfaces:

- Harsh chemicals and solvents can damage powder coating. Once damaged, the surface is a lot more vulnerable to fading and failure.
- We recommend regularly inspecting your powder coat and wiping any dust off with a soft cloth. Clean, good quality micro-fiber cloths are recommended.
- We recommend regular washing with highly diluted mild soap and water. Use a soft towel to gently clean. Rinse and dry with another soft towel.
- If your powder coat is losing its shine, you can apply a thin layer of high-grade non-abrasive car wax after it's been cleaned. Wipe all the wax off once its dried and the powder coat should look like new again! Use a car wax brand that contains a UV blocker or UV inhibitors. Do not use compound-type waxes as they contain abrasives that can harm the powder coating.

It's important in coastal areas to regularly clean any powder coated surfaces as salt will stick to the coating, dulling its appearance. This can leave your powder coated surface looking chalky.

We don't recommend paint touch ups to cover imperfections as paint won't adhere to powder coated surfaces. A local professional can quote to repair the powder coating.

How do I maintain my Powerfold mirrors?

Under normal Powerfold operation, there shouldn't be any maintenance required. However, if it is regularly used off-road, then the mirrors may need to be maintained every 12 months. This maintenance involves pulling the mirror into the fully extended position and applying dry lubricant on the arms.

Maintaining your Chrome Mirrors

The chrome finish used on our mirror heads is a chrome plated plastic, which provides the appearance and feel of real chrome, in a more lightweight and cost-effective material.

Weather conditions, how often they are washed and how close to the ocean you live, all play a role in the longevity of the chrome finish.

- Automatic car washes that use bristle brushes or acidic preparations can damage your chrome
- Salt and de-icers will surface pit chrome and extra care will be required with more frequent washes to remove residue.
- We recommend washing them weekly with mild soap and water, steering clear of ammonia-based or acid solutions.
- Clean, good quality micro-fiber cloths are recommended to wipe down the chrome surface and prevent water stains from forming
- An occasional polish with a non-abrasive chrome polish will help bring your chrome back to its original shine!

If chrome isn't properly maintained, it can develop pitting from corrosion or lose its attractive shine. We recommend Autosol Metal Polish and Autosol Metal Life Saver

Compact Towing Mirrors

Non-Extended Standard Driving Position



Extended Towing Position




Fully Extended Towing Position




Next Gen Towing Mirrors



Non-Extended Standard Driving Position



Extended Towing Position



Fully Extended Towing Position





Your adventure awaits...
Let's Begin!

Step 1

Prepare vehicle:

Place transmission into park position with handbrake on.

Turn ignition on and lower front door glass/windows.

Turn ignition off and remove key.




Step 2

Remove corner door trim:

Remove Phillips head screw from door upper corner trim.

This will enable the plastic clip securing the trim to be removed.



Remove the corner trim using your hands.



This will reveal 1 of the 3x M10 Hex head mirror head retaining screws. The other 2 Hex head screws attaching the mirror are revealed after taking door panel off (Step 12).

Step 3

First door panel screw:

FOR ISUZU D-MAX AND MU-X:



Using the soft plastic pry-bar, insert and lever the small door trim cover behind the door handle.

This will reveal a single phillips head screw.

FOR MAZDA BT-50:



Using the soft plastic pry-bar, gently remove the plastic panel.



Using the soft plastic pry-bar, insert and lever the small door trim cover behind the door handle. This will reveal a single phillips head screw.

Step 4

Second door panel screw:



Remove the arm rest cover by lifting upward and outwards, using your hands.

This will reveal the second single phillips head screw.

Step 5

Third door panel screw:



Remove the window operating push-button trim, using the soft plastic prybar, by inserting as shown and levering upward.

This will reveal the third single phillips head screw.

Step 6

Keep screws:

Using a phillips head screwdriver, remove the 3 revealed screws which hold the door trim in position.

Ensure that you retain these 3 screws and when required you re-insert into the same position you removed them from.

Note: The 2 arm cover screws have a washer attached to the screw.



Step 7

Remove door panel:



Insert the soft plastic pry-bar under the bottom rear corner of the door trim.



Lever the door trim outward to disconnect from all retaining clips.



Note that the door trim must remain electrically connected to the vehicle door.

Lift the door trim upward and position onto 'S'-hook, to support the door trim during installation.

Step 8

Disconnect door wiring:

You now have access to the mirror electrical connection which you will disconnect.

Disconnect the single white connector.




Step 9

Remove the mirror:

With ratchet and 10mm socket, remove the 3x M10 Hex Head, mirror head mounting screws.

Support the mirror during this operation.



Remove the mirror from the doors, threading the electrical connector through the opening.




HANDY TIP: Keep your original OEM mirrors as back up should something happen to one of your Clearview Mirrors, necessitating the need to return it to us for repairs.

Step 10

Remove the Towing Mirror etc. from the shipping box:

Remove complete mirror heads from box.

Remove all 3x M10 hex head screws from the mirror base and retain for Step 12.



Step 11

Attach the Towing Mirror to the Vehicle:



For ease of handling the Towing Mirror during installation, extend the mirror head to the mid-position.



Present the Towing Mirror head base to the door panel mounting position.

Feed the electrical wiring and connecting plug, through the central opening.

Align the Towing Mirror Head Base to the 3 mounting holes in the door panel.


Push the Towing Mirror head base fully home and ensure that the electrical wiring is pulled fully through, this is to avoid trapping of the wiring between the door panel and the mirror base when the screws are secured.

Hand-start the 3x M10 hex head screws, to avoid cross threading of the screws.




Step 12

Tighten screws and connect wiring:



With the ratchet, fully tighten all 3x M10 hex head screws to secure the Towing Mirror head to the vehicle door.



Connect the Towing Mirror single white connection plug to the door wiring.

Step 13

Test mirrors:

Before re-assembling the door trim, check the Towing Mirror functions.



Turn the ignition on and operate the mirror glass movement, using the operating push buttons on the door trim.

Check the operation of the indicators on each side as well as the hazard lights. Once confirmed OK, turn the ignition off

Step 14

Re-assemble the door trim:



Lift the door trim off the 'S'-hook and position back onto the door.

Tap around the edges of the door trim to secure the door trim into the retaining clips.

Step 15

Secure door trim:

Secure the door trim into position using the same 3 Phillips head screws removed in steps 3, 4 & 5. Ensure that the screws are returned into the same position from where they were removed.



Step 16

Fix remaining panels:

Door upper corner trim (Step 2).

Small trim cover (Step 3) and
the arm rest cover (Step 4).

Push each of these trims into position and ensure they are secure, using your hands.
Re-insert the plastic clip and screw previously removed in Step 2.

Congratulations! You have now fully installed your new Clearview Towing
Mirrors and are ready for your next adventure!



Can I install Clearview mirrors myself?

Yes! Depending on the complexity of the installation, Clearview mirrors are extremely easy to install and mount to the vehicle's original OEM mirror mounts. Depending on the vehicle's current mirror options, Clearview mirrors include plug-and-play wiring looms. Instructional videos are also available on our website (clearviewaccessories.com.au) in the 'HOW TO' section. Clearview recommends that any installation requiring hard wiring be done by a licensed auto electrician.

What is the fitting time?

Depending on the complexity of the installation, the fitting will vary from vehicle to vehicle. Any installation requiring any special fittings and/or hard wiring will require longer fitting times (eg. 360° Camera fitting/calibration, any electric hard-wiring kits, OAT sensors, and any other complex installations etc).

NB: Fitting times will also vary depending on the skillset or capabilities of the fitter.

Please contact Clearview Accessories if you have any questions about fitting or wiring.

Are the telescopic arms electric?

No. The telescopic arms are extended manually. Clearview Mirrors will only fold against the vehicle electronically provided we make that model in Power Fold.

Can I retrofit the original mirror base to the Next Gen or Compact mirrors?

No. The cost of converting the mirrors to suit the new models is not worth it. We recommend either selling your Original mirrors privately or through the 'Pre-Loved' section (Within the 'Shop' menu category) of our website and purchasing the new Next Gen or Compact mirrors brand new.

Can I add an indicator later if I didn't order the mirrors with an indicator?

Yes, you can. But it comes at a greater expense than if you were to order the mirrors with indicators. Installation of the mirror head will require a longer time and more parts to dismantle.

Are spare parts available?

Yes. We have a list of spare parts for all our mirrors on our website. Our dealers also have a list of all our spare parts. If you cannot find the parts that you require, please contact Clearview Accessories, or any of our dealers to assist you with your enquiry.

How do I maintain my mirrors?

We recommend that Clearview Mirrors are lubricated every 6-12 months, when the arms feel stiff during use, or after any big trip to ensure longevity of your Clearview Towing Mirrors!

This maintenance includes pulling the mirror into the fully extended position and applying the dry lubricant on the arms. We recommend using WD-40 Specialist Dry Lubricate.

Avoid any waxy lubricants as they can attract dirt and grit.



**SCAN THE QR CODE
AND VIEW OUR VIDEO
DEMONSTRATING**

How to lubricate the arms
on Clearview Towing Mirrors



I have just installed my new Powerfold mirrors and the mirror heads appear 'loose'/‘floppy’.

After the mirrors are installed, they need to be cycled a few times. This will allow all the internal mechanisms to set and find the proper positions.

- If the mirror head is still loose/floppy after they're cycled, please contact Clearview Technical Support.

I have installed my Powerfold Mirrors and have noticed that the Passenger's side mirror is closer to the vehicle compared to the Driver's side; Is this normal?

This is entirely normal. In most vehicles, the mirror housings are angled differently between the driver's and passenger's sides.

- This is because when you sit in the car, the mirrors are positioned from/to the driver's position (which is off-centre), so generally, the passenger side mirrors are closer to the vehicle body to allow you to have the same field of vision in the mirror.

One of my Powerfold Mirrors folds/opens quicker than the other one; Is this normal?

Generally, the passenger mirror will fold/open quicker, as it is closer to the vehicle body and therefore travels a shorter distance compared to the driver's side mirror. See previous question in regards to why the mirrors are angled differently.

My mirrors have been knocked out of Driving Position; how do I fix it?

Press the powerfold switch once. This should initiate the powerfolding motors and the mirrors should start folding inwards. Wait until the mirrors are fully folded in and have stopped moving, then press the powerfold switch again. This should now bring your mirrors back out to normal driving position. Check and see if the mirrors are locked into position firmly. If the mirror is not returning to the normal position, please contact Clearview Technical Support.

Note: The Powerfold mirrors can fold manually, however the manual fold mechanism is only designed as a safety feature. Through the lifespan of the product, manual folding will occur, such as people walking into them or accidentally bumping them. The internal mechanisms are designed to withstand this accidental manual folding during normal usage. It is not recommended for the mirrors to be manually folded constantly, as it will prematurely wear out the internal folding mechanisms and reduce the lifespan of the product.

My mirror was knocked out of driving position. When I cycled them, there is a clicking sound and the mirror appears to have “jumped”; Are my mirrors damaged?
When the Powerfold mirror is being cycled to find its original driving position, it will “jump” back into position and make an audible click sound when mechanisms realign. Once the mirrors have found the original position and have been cycled, check for looseness and mirror movement. If they feel firm, then the mirrors have not been damaged. If they still feel loose, please contact Clearview Technical Support.

Why don't my mirrors fold all the way in/out when I press the switch?

The circuit breaker inside the mirror activates when the electrical current increases due to resistance. If the mirror stops before it reaches the folded in/out position, that means something is adding resistance while the mirrors are folding, hence activating the circuit breaker before it has reached the desired position. Please contact Clearview Technical Support.

Clearview Towing Mirrors are full replacement towing mirrors designed and manufactured to the highest quality standards to replace your vehicle's standard side mirrors. We stand behind our Next Gen and Compact Towing Mirrors with a 3-year Manufacturer's Warranty and 7-year Parts Warranty. We stand behind our Original Towing Mirrors with a 12-Month Manufacturer's Warranty and 3-year Parts Warranty. Clearview Accessories warranty applies to the original purchaser only.

Please ensure that your receipt is kept in a safe place. A receipt will be required to make a warranty claim on any Clearview product. If we determine that a Clearview Towing Mirror is defective in materials or workmanship during the Warranty, we will either repair or replace the product. Repair or replacement is solely at the discretion of Clearview Accessories.

Please ensure that you fit the Clearview products in accordance with the product information provided and all relevant vehicle safety and compliance laws; and use the Clearview product for the purpose for which it was originally designed. This warranty does not apply to failure or damage caused by incorrect or faulty fitment, accidental or intentional damage, alteration, acts of nature, vandalism, collision, road hazards or adverse conditions, misuse, abuse or neglect of the Clearview product, including improper repair or maintenance or failing to repair and maintain the product, failure of other products, operation of the product outside of its environmental or technical specifications, or repair or modification carried out by anyone other than Clearview Accessories. No charges will be accepted for external labour or materials without the prior advice or clearance from Clearview claims team. Clearview Accessories warranty does not cover any scratches or chips.

Clearview Towing Mirrors are designed to be vehicle specific. When purchasing Clearview Towing Mirrors, carefully select your product according to ADR compliance laws and vehicle specifications. Clearview Towing Mirrors are not designed to be modified for convenient use on alternative vehicles. Alteration, modification, or manipulation of our products will void all warranty with Clearview Accessories.

All claims under this warranty should be lodged through our website warranty section <https://www.clearviewaccessories.com.au/about/warranty/> with the detail of the fault, proof of purchase, proof of identification and vehicle fitment details where relevant. If your claim is accepted for defects in material or workmanship Clearview will, at its discretion, offer to repair, replace parts, or return and refund.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. In the event of a minor failure, the company reserves the right to choose to repair or replace the product.

Clearview Towing Mirrors, ABN: 59 140 145 393, 3 Frog Court, Craigieburn VIC 3064 Ph: (03) 8351 9933 Email: info@clearviewaccessories.com.au





Head Office

3 Frog Court, Craigieburn
VIC 3064, Australia
(03) 8351 9933

QLD Office

Unit 1/49 Doherty Street, Brendale
QLD 4500, Australia
(07) 3204 7693

info@clearviewaccessories.com.au

clearviewaccessories.com.au

